



Calogic, LLC  
 237 Whitney Place  
 Fremont, CA 94539  
 Tel: 510-656-2900  
 Fax: 510-651-1076

JFET Amplifier Applications (High Gain)						
P/ N	I <sub>dss</sub> (mA(min))	I <sub>gss</sub> (pA(max))	g <sub>fs</sub> (mS(min))	eN (nV/ rootHz(typ))	Package	Channel
2N4416/A	5.0	-100	4.5	10	TO-72	N
2N5484	1.0	-1000	3.0	20	TO-92	N
2N5485	4.0	-1000	3.5	20	TO-92	N
2N5486	8.0	-1000	4.0	20	TO-92	N
J210	2.0	-100	4.0	5	TO-92	N
J211	7.0	-100	6.0	5	TO-92	N
J212	15.0	-100	7.0	5	TO-92	N
J270	-2.0	200	6.0	20	TO-92	P
J271	-6.0	200	8.0	20	TO-92	P
J308	12.0	-1000	8.0	5	TO-92	N
J309	12.0	-1000	10.0	5	TO-92	N
J310	24.0	-1000	8.0	5	TO-92	N
PN4416	5.0	-100	4.5	10	TO-92	N
SSTJ210	2.0	-100	4.0	5	SOT-23	N
SSTJ211	7.0	-100	6.0	5	SOT-23	N
SSTJ212	15	-100	7.0	5	SOT-23	N
SST270	2.0	200	6.0	20	SOT-23	P
SST271	6.0	200	8.0	20	SOT-23	P
SST308	12.0	-1000	8.0	5	SOT-23	N
SST309	12.0	-1000	10.0	5	SOT-23	N
SST310	24.0	-1000	8.0	5	SOT-23	N
SST4416	5.0	-100	4.5	10	SOT-23	N
U308	12.0	-150	10	5	TO-52	N
U309	12.0	-150	10	5	TO-52	N
U310	24.0	-150	10	5	TO-52	N